




Lenovo Product Carbon Footprint (PCF) Information Sheet

PC/Notebook/Monitor/Tablet

Commercial Name	ThinkStation P340 Tiny	
Model Number	30DE, 30DF, 30DG, 30DR, 30DS	
Issue Date	2022/05/19	

Product Environmental Attributes																							
(a) Product Carbon Footprint Value:	582 kg of CO ₂ e (see Note 1 below)																						
(b) Product Picture:	(c) Life Cycle Detail by Component & Life Stage (Pie Chart):																						
	 <table border="1"> <caption>Life Cycle Detail by Component & Life Stage (Pie Chart Data)</caption> <thead> <tr> <th>Component / Life Stage</th> <th>Percentage</th> </tr> </thead> <tbody> <tr> <td>Use</td> <td>44%</td> </tr> <tr> <td>Mainboard and other boards</td> <td>26%</td> </tr> <tr> <td>Power Supply Unit</td> <td>17%</td> </tr> <tr> <td>Transportation</td> <td>5%</td> </tr> <tr> <td>Solid State Drive</td> <td>4%</td> </tr> <tr> <td>Chassis</td> <td>4%</td> </tr> <tr> <td>EoL</td> <td>0%</td> </tr> <tr> <td>Optical Drive</td> <td>0%</td> </tr> <tr> <td>Hard Drive</td> <td>0%</td> </tr> <tr> <td>Packaging</td> <td>0%</td> </tr> </tbody> </table>	Component / Life Stage	Percentage	Use	44%	Mainboard and other boards	26%	Power Supply Unit	17%	Transportation	5%	Solid State Drive	4%	Chassis	4%	EoL	0%	Optical Drive	0%	Hard Drive	0%	Packaging	0%
Component / Life Stage	Percentage																						
Use	44%																						
Mainboard and other boards	26%																						
Power Supply Unit	17%																						
Transportation	5%																						
Solid State Drive	4%																						
Chassis	4%																						
EoL	0%																						
Optical Drive	0%																						
Hard Drive	0%																						
Packaging	0%																						

Note 1:

All estimates of carbon footprint are uncertain. Lenovo reports the 95th percentile of the carbon footprint estimate to reflect that uncertainty. For this product, that estimate has a mean of 441 kg of CO₂e and standard deviation of 84 kg of CO₂e. For a quantity that follows a normal distribution, the 95th percentile value is equal to the mean plus the standard deviation multiplied by 1.64. Other organizations might report this value as 441 +/- 84 kg of CO₂e.

This PCF was generated using the Product Attribute to Impact Algorithm model, Version 1/20/2018, Date: 1/20/2018 (Product Type: Workstation), © Massachusetts Institute of Technology's Materials Systems Laboratory, August 2012. Please refer to the Intended Uses and Limitations of the PAIA Model, © Massachusetts Institute of Technology's Materials Systems Laboratory, August 2012 for further details. [Link to Document](#)

This calculation was based upon a ThinkStation P340 Tiny with the assumptions and configuration described in the calculation assumptions in the next page.

This pie chart provides the percent contribution of the mean value for each element of the analysis for the full life cycle CO₂e impacts of the product. Individual elements displaying 0% are less than 0.5%.

Assumption Table					
Category	Element	Unit	Input	Mean	COV
Product Specifics	Product Weight	kg	Input	1.4	Primary Data
	Form Factor	no unit	Tiny/Mini		
	Screen Size	inches	Default		
	Product Lifetime	years	Input	5	Low COV
Location	Assembly Location	no unit	CN		
	Use Location	no unit	WW		
Transportation from Assembly to Customer	To country of use: by air	fraction	Input fraction	.25	Low COV
	To country of use: by ship	fraction	Input fraction	.75	Low COV
	To country of use: by rail	fraction	Input fraction		Low COV
	To country of use: by truck	fraction	Default		
	In country of use: by air	fraction	Input fraction	.1	Low COV
	In country of use: by ship	fraction	Default		
	In country of use: by rail	fraction	Input fraction	.2	Low COV
	In country of use: by truck	fraction	Input fraction	.7	Low COV
End of Life	Fraction Recycled (remainder to landfill)	fraction	.8		Low COV
	Fraction Shredded Recycling (remainder to manual)	fraction	.2		Low COV
The PCF value is calculated using the specific attributes above for assembly, use and transportation mode. If you need any other country specific information, please contact environment@lenovo.com .					

Notes:

Life cycle phases included in the streamlined Product Attribute to Impact Algorithm (PAIA) Life Cycle Analysis (LCA) can be grouped into four categories which include Manufacture, Transport, Use, and End of Life. Below is a brief description of each phase.

Manufacture: This life cycle phase captures emissions generated during the extraction, production, and transport of raw materials, the manufacture of components and subassemblies (including the product packaging) and product assembly.

Transport: Emissions included in the transport phase include all those generated during the air, ocean or land transport of finished or semi-finished Lenovo products between Lenovo facilities and from Lenovo facilities to customers.

Use: In use energy consumption is calculated in accordance with the U.S. Environmental Protection Agency's Energy Star® Typical Energy Consumption (TEC) methodology. Calculated energy consumption is then used in combination with average emissions factors for the designated country of use to calculate emissions.

End of Life: It is assumed that a designated portion of the product (see table above) is recycled at the end of the use period determined in the TEC methodology. It is also assumed that the balance of the product waste materials is disposed of by landfill. Emissions generated during the mechanical destruction, separation and transport of end of life materials are included in the calculation.

Product scope of this sheet includes desktop computer, integrated desktop computer, notebook computer, monitor and tablet. This document is only valid in connection with "THE ECO DECLARATION" of the specific product.